

# **Electro Contact Cleaner**



# cleans and degreases electronic or mechanical components

WEICON Electro Contact Cleaner is a special cleaner for the fast and effective cleaning and degreasing of all kinds of soiled or corroded contacts.

Electro Contact Cleaner was specially developed for the cleaning of electronical and mechanical components. The special formula with high-purity solvents removes oxide/sulphide layers, combustion residues and resinous or sooty soiling.

WEICON Electro Contact Cleaner reduces voltage loss and increases electric conductivity. Contamination that can cause tracking current is removed. It can be used on electro-technical or mechanical components such as electrical machines, measuring instruments, tools, balances, switches and sensors or electrical connections, contacts, relays and switchboards.

# **Technical Data**

Odour	solvent
Features	high-purity solvents
Storage stability	24 months
Colour	colourless
AOX-free*	Yes
ISSA-Code	53.402.22
IMPA-Code	450808

Before applying Electro Contact Cleaner, disconnect electric devices from the power line and wait for some minutes until there is no more electric tension inside the machine. Spray a sufficient quantity onto the parts to be cleaned from a distance of 25-30 cm. Electro Contact Cleaner evaporates very quickly and does not leave any residues. Wiping or brushing supports the cleaning effect. Devices should be switched on only when both propellant and active substance have evaporated completely.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding +50°C.

# Safety and health

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

### Available sizes:

11210400 Electro Contact Cleaner 400 ml

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.